

Section 300 Definitions

Lot, Backlot. A lot that does not have the required minimum Frontage directly on a public street and meets the standards of Section 529 Lot, Backlot. (See Sec. 500 Performance Standards)

529 Lot, Backlot

A. Zoning Districts. Backlots shall be permitted in the following zoning districts:

- Farm
- Farm-Residential
- Light-Density Residential
- Medium-Density Residential

B. Standards. The following standards shall apply to the creation of backlots, or the extension of existing backlot right-of-ways:

1. General Standards. The following general standards apply to backlots:

(a) Rights-of-Way.

(1) Backlots must be accessed by a right-of-way having a minimum width of fifty (50) feet. The required minimum width must be continued for the entire length of the right-of-way.

~~(2) A right-of-way shall serve no more than one (1) backlot.~~

~~(23) Extension of a right-of-way to serve additional~~ A right of way serving more than one (1) backlots shall meet the applicable street construction standards of Section 550.

~~(ii) If the addition of lots on a right of way falls within a different street standard, the entire right of way shall be improved in accordance with the street standards in Section 550.~~

~~(34)~~ A hammerhead turnaround shall be provided in accordance with Section 550(B)(8)(f)(2).

~~(45)~~ Right-of-Way Extensions:

- The first hammerhead created after March 12, 2012 may be retained as part of the right-of-way and may continue to be used to meet the minimum frontage requirement of the zoning district. Hammerheads created prior to that date will not be required to be removed, even if this results in more than one hammerhead on a right-of-way.
- All subsequent hammerheads created after March 12, 2012 shall be removed if a road is extended beyond the location of said existing hammerhead turnaround(s). After the hammerhead turnaround is removed, all lots must continue to comply with the minimum frontage requirement of the zoning district.

Commented [KMC1]: This seems unnecessary, if the intention is to require any ROW serving more than one backlot to meet the standards.

- (b) Frontage. The backlot shall meet the minimum frontage requirement of the applicable zoning district along the right-of-way.
- 1) All sides of a hammerhead turnaround right-of-way may be used in the calculation of frontage. If the hammerhead turnaround is removed to accommodate future right-of-way extensions, the original lot must still meet the minimum lot frontage requirement.
- (c) Minimum Setback Requirements
- (1) The required minimum front setback standard for structures constructed on a backlot shall be measured from the closest edge of the right-of-way.
 - (2) Minimum setbacks from a new right-of-way do not apply to structures on abutting properties that do not obtain their frontage from said right-of-way.
 - (3) Front Lot Line. For purposes of determining the front lot line, and the front setback, the right-of-way shall be deemed to run from one side of the lot to the other side of the lot if it ends prior to that point. *(See Diagram A)*
 - (4) Corner Lots. If a corner lot is created by the installation of a right-of-way, the minimum setbacks shall be met in accordance with the corner lot standards in Section 500. The installation of a hammerhead turnaround does not constitute the creation of a corner lot. Backlots that obtain their frontage from a hammerhead turnaround shall choose which side of the hammerhead turnaround will constitute the front lot line. The designated front lot line shall be stated on the building permit and shall not be changed after said designation. *Note: If a choice of front lot lines is available, care should be taken to plan for the setback requirements necessary for future right-of-way extensions.*
- If the minimum setbacks for corner lots cannot be met, the applicant may apply for a dimensional variance in accordance with Section 1100 of this Ordinance.
- (5) No dwelling unit shall be erected on a backlot that is closer than two hundred (200) feet from an existing public street, private road or private way.

Commented [KMC2]: This could use some clarification as to whether this is measured from nearest lot line or from dwelling. Perhaps "any accessible boundary of which is located closer than 200 feet..."?

Diagram A
Front Lot Line

